

waterproof Stroboscope (IP68)

Art.Nr.: 1189

trouble-free, processor-technologie, precise fine adjustment of flash frequency by foil key pad with cursor setting, standby with data-hold function, restart with last measured value by tipping any arrow key, automatic power "OFF" with last measured value stored, stabilized voltage, temperatur constant.

General Data:

Light Source: flash bulb, internal
Flash bulb: socket mounted Xenon-longlife
Light intensity: max. 680 Lux in 50cm distance from reflector (beam axis)
Flash duration: ca. 2 - 7 μ s
Frequency range: 1 - 335 Hz = 60 - 20100 RPM (min-⁻¹)
with automatic flash power control
internal oscillator

Trigger action: adjustable via foil pad with cursor function, standby (after 2minutes)
- Internal control: with data-hold function, automatic switch-off with storage function of the last set value.
via LC Display selectable in Hz (flashes per sec.) or RPM (min-⁻¹)

Display: last set value
Memory: < \pm 0.1% of set value
Accuracy: automatically
Flash power control:

Technical Data:

Power supply: 12V DC (NiMH Accu)
Power consumption: max. 25W
Aluminium / IP68 (keypad IP65)
Housing: Housing: length = 250mm, diameter = 82mm,
Dimensions: handle bar: height = approx. 60mm, length = 200 mm
Weight: 1,5 kg

MOVISTROB MS 2800-WD



Accessories:

Prozessor controlled plug charger Type B11523
Spare flash bulbs

Note:

Internal control / trigger action without standby and automatic switch-off on request (constant power).

